

**BRUSH & TROWEL GRADE MASTIC****Product Specification Sheet**

SUPERSEAL Brush & Trowel Grade Mastic's are a highly advanced, water-based, fibered mastic emulsion for use in foundation waterproofing and dampproofing applications.

USES & FEATURES

SUPERSEAL Brush & Trowel Grades Mastic are used in foundation construction to repair or seal tie holes, protrusions, cold joints, honeycombs, rock pockets, curbs, gaps, and fissures in foundation construction applications.

- It cures to a firm self-adhering patch for Waterproofing or Dampproofing to be applied over.
- It can be used inside or outside.
- It's environmentally friendly and has no solvents or harsh chemicals.

CONDITIONS OF USE

- Apply to clean and debris free surfaces.
- Apply above freezing and rising in temperature.

PART #	
BG00500	5 Gallon pail Brush Grade Mastic (18.9L)
TG00005	5 Gallon pail Trowel Grade Mastic (18.9L)

<u>PROPERTIES & TESTING</u>	TECHNICAL DETAILS
PHYSICAL PROPERTY	
Type	Water-based fibered mastic emulsion.
Color	Brown curing to Black
Solids	64%
Thickness	20 mils / 0.5 mm dry
Curing Time	8 to 24hr at 70 °F (20 °C), 50% relative humidity.
Application	Brush or roller, above freezing and rising.
Storage Temperature	45 to 110 °F (7 to 45 °C)
Shelf-Life Stability	24 Months, above 45 °F (7 °C)

TEST CRITERIA	TESTED TO	RESULTS
Resistance to Water	ASTM C836; ASTM D466	Pass
PH		Approx. 8.5
Remain in Place During Application	ASTM C836-06	Pass
Hydrostatic Pressure Over Cracks	ASTM C1306-00	4 psi / 30 mil
Low Temperature Crack Bridging	ASTM C836-06; ASTM C1305/C1305M-16	Pass
Low-Temp Flexibility at 32 °F / 0 °C	ASTM C836	No cracking or flaking
Peel Adhesion after Water Immersion	ASTM C836-06	Pass
VOC's	Not regulated - water based	36 g/L

Please go to www.superseal.ca for the current Product Data Sheets.

